

Frame Cramp Dowel Hole

Lateral Restraint Products

These products allow masonry walls to be restrained back to other elements of the structure. This could be pre-existing walls, or new or pre-existing steel work. The ties, once in position, prevent sideways movement between a wall and another structure.



Frame Cramp Dowel Hole

Frame cramp with 3 x 6.5mm holes in the projection for a dowel bar. Used to restrain stone cladding and coping stones. Dowels normally supplied separately, but can be fixed into the tie for easy installation.

Normally used with 6mm

dowel. Sizes:	40mm	175mm
	50mm	200mm
	75mm	225mm
	100mm	250mm
	125mm	275mm
	150mm	300mm

Performance

Tested over 120mm Cavity	
Tension Capacity	7760N
Compression Capacity	1310N

Safety Precautions

Frame Cramps with Dowel Holes are manufactured from sheared plate and strip so may contain sharp edges. Suitable personal protection should always be used when handling/installing these products.

BS Fixings

BS Fixings

BS Stainless Limited
360 Leach Place, Walton Summit
Bamber Bridge, Lancashire
PR5 8AS, United Kingdom
Tel: +44 (0) 3330 117818

Fax: +44 (0) 1772 313010
info@bsfixings.co.uk
www.bsfixings.co.uk