

Banding Tools

Product Description/ Specification



Standard Banding Tool is used to fix stainless steel banding and strapping through to the operation to tighten. This is ideal for various applications of banding including Bandfix® Sign Banding, often used with a sign to band it to a post similarly with bins often used by councils to secure the bin to a post. These can also be used for cables, metal insulation, packing etc. with our Bandfix® Value band or heavier insulation products. These are regularly used on industrial Oil and Gas Pipeline Insulation by metal ladders to hold metal securely around pipework or tanks. The tools tensions over 1100 kg (2,400 lbs) and cuts off the spare banding.

BS Stainless do 3 different designs of these tools:

- Standard Banding Tool, Giant Banding Tool—These are also referred to as a "Whirley Bird" bander
- Tensioner Banding Tool

Tools are used to apply stainless steel bandings, but can also be used with Galvanised or carbon steel banding and general steel strapping.

Designs and Specification

		
Standard Tool	Giant Banding Tool	Tensioner Banding tool
Light Weight Application	High Tension Wide Bands	High Tension wider Bands
Widths—9mm (3/8") to 20mm (3/4")	Widths—19mm (3/4") to 32mm (1¼")	Widths—9mm (3/8") to 20mm (3/4")
Weight 2kgs approx. (4.3lb)	Weight 5kgs approx. (12.3lb)	Weight 2kgs approx. (4.3 lb.)
Heat treated tool with built in cutter	Heat treated tool with built in cutter	Includes cutter and hammer
Spring loaded grip lever for ease of use	Spring loaded grip lever for ease of use	Maximum Thickness 0.03" (0.76mm)
Corrosion resistant blue epoxy coating	Corrosion resistant epoxy coating	Epoxy coated handles for good grip

For full details on application, please refer to BS Stainless 'Banding Tool Instructions'